

CERTIFICATE OF COMPLIANCE

Certificate Number 20171206-E44653
Report Reference E44653-20151218
Issue Date 2017-DECEMBER-06

Issued to: SIEMENS AG
DF CP R&D VC 2
WERNER-VON-SIEMENS-STRASSE 48
92224 AMBERG GERMANY

This is to certify that representative samples of AUXILIARY DEVICES
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 508 and CSA C22.2 No. 14-13, Industrial Control Equipment.

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20171206-E44653
Report Reference E44653-20151218
Issue Date 2017-DECEMBER-06

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Addendum -

Product Covered:

USL, CNL, Auxiliary Devices, Potentiometer, – Cat. No. 3SU1200-2P or 3SU1250-2P, followed by Q through Z, followed by 10, followed by 1, followed by A, followed by A, followed by 0, followed by a suffix of numbers or / and letters for manufacturers use only.

USL, CNL, Auxiliary Devices, Toggle switch, Selector switch - Cat. No. 3SU10 or 3SU11, followed by 0, 3, or 5, followed by 0, followed by 2 or 7, followed by A or B, followed by A, B, C, D, E, F, or S followed by 10 up to 88, followed by 0, 1, or 3, followed by A up to P or any variations,, followed by A, followed by a suffix of numbers and / or letters for manufactures use only.


USL, CNL, Accessory Holder, 4 poles, Cat. Nos. 3SU1500-0BA10-0AA0 and 3SU1550-0BA10-0AA0

Ratings:

Potentiometers - Resistor Value

Q through Z, ranging from 1 kΩ up to 470 kΩ

Environmental Designations: Type 1, 2, 3, 3R, 4, 4X, 12, and 13



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20171206-E44653
Report Reference E44653-20151218
Issue Date 2017-DECEMBER-06

NOMENCLATURE BREAKDOWN: Potentiometer

3SU1200-2P	Q	10	-1	A	A	0	Z
I	II	III	IV	V	VI	VII	VIII

1. Basic Type
3SU1200-2P Potentiometer, plastic
3SU1250-2P Potentiometer, metal
2. Resistor Value

Q through Z, ranging from 1 kΩ up to 470 kΩ
3. Color
10 black
4. Type of Terminal
-1 Screw terminal
4. Function
A without designation
6. Inscription
A without inscription
7. Manufacturer's identification
Followed by a letter e.g. 0 Standard
8. Appendix

Followed by a suffix of letter and or number



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20171206-E44653
Report Reference E44653-20151218
Issue Date 2017-DECEMBER-06

NOMENCLATURE BREAKDOWN: Toggle Stick / Selector Switch

3SU10 0 0 -7 A A 10 -0 AA 0
I II III IV V VI VII VIII IX X

I. Basic Type

3SU10 - actuator
3SU11 – complete device

II. Design

0 – Plastic
3 - Plastic / Metal version
5 – Metal version

III. Illumination

0 - without

IV. Type of actuator

2 – Selector switch / knob
7 – Toggle Stick

V. Kind of Handling

A - without centerlock
B - with centerlock

VI. Function

A - 2 positions, horizontal, maintained
B - 2 positions, vertical, maintained
C - 2 positions, horizontal, momentary
D - 2 positions, vertical, momentary
E - 4 positions, maintained
F - 4 positions, momentary
S – 4 positions, latching 4x90°


VII. Color

00 up to 99 representing color

e.g 10 – Black
e.g 88 - Silver

VIII. Type of Terminal

-0 without terminal
-1 screw terminal
-3 spring loaded terminal



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20171206-E44653
Report Reference E44653-20151218
Issue Date 2017-DECEMBER-06

IX. Mounting Arrangement


- A - no module no holder
- B – 1 contact, normally open (1NO)
- C – 1 contact, normally closed (1NC)
- F – 1 contact, normally open or closed (1NO/NC)
- L – 2 contacts, normally open or closed (2NO/NC)
- M, N, P, 2 contacts, normally open and normally closed (1NO, 1NC)

X. Inscription

- A - without inscription
- . - or any other customers required markings

XI. Manufacture's identification

- 0 up to 9
- 0 - Standard version e.g



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

