



SIEMENS



SIRIUS 3SK safety relays



## The starter kit for more complex safety applications

SIRIUS 3SK2 safety relay complete with  
SIRIUS Safety ES parameterization software

It's a safe bet you'll be impressed by the package that we've wrapped up for you. It contains everything you need for implementing even more complex safety functions with a level of simplicity that is typical of SIRIUS: a 22.5 mm wide, software-programmable 3SK2 basic unit, the associated SIRIUS Safety ES Standard software that requires no programming knowledge, and a USB cable.

**After all: Safety is a SIRIUS business.**



[siemens.com/safety-relays](https://www.siemens.com/safety-relays)

# Don't miss out on this all-in-one package – The benefits for you at a glance

## SIRIUS 3SK2 basic unit

- Maximum functionality: up to 10 fail-safe inputs in an overall width of just 22.5 mm
- Selective tripping of up to four safety applications by means of independent outputs
- Flexibly expandable with 3SK1 output expansions that require minimal wiring effort – using device connectors
- Seamless integration of the SIRIUS 3RM1 motor starters – likewise using device connectors
- Individually selectable time functions
- Easy software parameterization – no programming knowledge required

## SIRIUS Safety ES Standard

- Easy setup of complex safety applications using the drag and drop method
- Efficient commissioning using test mode, forcing and extensive diagnostics

## USB PC cable

- Easy and comfortable transfer of configuration into device via USB

## Ordering data:

### SIRIUS 3SK2 basic unit

+ Software  
SIRIUS Safety ES Standard

+ USB PC cable

Article No. 3SK2941-2AA10



You can find up-to-date information at: [siemens.com/safety-relays](http://siemens.com/safety-relays)

Siemens AG  
Digital Factory  
Control Products  
P.O. Box 23 55  
90713 Fuerth  
Germany

Subject to change without prior notice  
02/16  
Article No.: DFCEP-B10043-00-7600  
Dispo 27601  
170/78704 SB 02162.  
Printed in Germany  
© Siemens AG 2016

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.  
All product designations may be trademarks or product names of Siemens AG or supplier companies whose use by third parties for their own purposes could violate the rights of the owners.